



## imageCLASS MF741CDW COPY · PRINT · SCAN · FAX · COLOR

## REVOLUTIONIZE TODAY'S WORKSPACE





- Speeds of up to 28 pages per minute in black/white & color
- First print-out in 7.5 seconds or less
- Print on-the-go with Apple® Airprint® and Google Cloud Print™
- ► Easily connect smartphone devices using Wi-Fi Direct
- User-friendly 5" color touch LCD
- Scan both sides of your document in a single pass

SERVICING SOUTH FLORIDA FOR OVER 10 YEARS

COMPLETEOFFICE.CO

## **SPECIFICATIONS**

Main Unit

Core Functions

Standard: Print, Copy, Scan, Send (Lite)

Item Code 3101C015 Processor

Canon Custom Processor

Control Panel 5" Color Touch Panel

Memory

Standard Interface Connection

USB 2.0 x2 (Host), USB 2.0 x1 (Device) High-Speed, 10/100/1000Base-T Ethernet (Network), Wi-Fi 802.11b/g/n, Wi-Fi ® Direct Connection

Paper Capacity (Letter, 20 lb. Bond)

Standard: 300 Sheets

Paper Sources (Letter, 20 lb. Bond) 250-sheet Paper Cassette, Standard:

50-sheet Stack Bypass Optional: 550-sheet Paper Cassette (Cassette Unit AF-1)

850 Sheets Maximum:

Paper Output Capacity (Letter, 20 lb. Bond)

75 Sheets Standard: Supported Media Types

Thin, Plain, Recycled, Color, Thick, Coated, Cassettes:

Label, Letter

Thin, Plain, Recycled, Color, Thick, Coated, Stack Bypass:

Label, Letter

Supported Media Sizes

A4, A5, B5, Letter, Legal, Statement, Cassettes:

Executive, Envelope: COM10, Monarch, C5, DL, Custom (Min. 3" x 5" to Max. 8.5" x 14") Letter, Legal, Statement, Executive

Envelope: COM10, Monarch, C5, DL Custom (Min. 3" x 5" to Max. 8.5" x 14")

Supported Media Weights

Cassettes: 16 lb. Bond to 53 lb. Bond (60 to 200 g/m<sup>2</sup>) 16 lb. Bond to 53 lb. Bond (60 to 200 g/m<sup>2</sup>) Stack Bypass:

Warm-up Time

Stack Bypass:

From Power On: 13 Seconds or Less From Sleep 6.1 Seconds or Less

Mode:

Dimensions (W x D x H)

18.8" x 18.8" x 18.4" Standard (Desktop): (478 mm x 478 mm x 467 mm)

23.7" x 18.8" x 23.2"

(602 mm x 479 mm x 589 mm)

Installation Space (W x D x H) 21.4" x 43.8" x 29" Standard

(Desktop): (544 mm x 1,112 mm x 736 mm) Fully

21.4" x 43.8" x 34.1

Configured: (544 mm x 1.112 mm x 866 mm)

Weight<sup>2</sup> Unit:

Approx. 64 lb. (29.0 kg) Boxed Weight: Approx. 76.1 lb(35 kg)

Supported OS

Windows 7/Windows 8.1/Windows 10/Windows Server 2008/Windows Server 2008 R2/Windows Server 2012/ Windows Server 2012 R2/Windows Server 2016 /

Mac OS X v10.9.5 (or later) What Comes In The Box

MF741Cdw Product, Cartridge 055 CMY Starter: 1,200 Yield/Black Standard: 2,300 Yield, Power Cord, Starter Guide, User Software DVD-ROM, Warranty Card

**Print Specifications** 

**Printing Method** Laser Beam Printing Print Speed 3

Up to 28 ppm (Letter); Up to 22.9 ppm (Legal)

First-Print-Out Time Approx. 7.5 Seconds

Recommended Monthly Page Volume

750 - 4,000 Pages Print Resolution (dpi)

600 x 600

Standard Page Description Languages

**Double-Sided Printing** Automatic (Standard)

**Direct Print** 

Available from USB Memory (JPEG, TIFF, PDF)

Printing from Mobile and Cloud-based Services <sup>4</sup> Apple® AirPrint,® Canon PRINT Business, Mopria™ Print

Service, Google Cloud Print™5

**Copy Specifications** 

Copy Speed

Up to 28 ppm (Letter); Up to 22.9 ppm (Legal)

First-Copy-Out Time (Letter)

Platen: 9.5 seconds/11.1 seconds (BW/Color) 9.9 seconds/11.8 seconds (BW/Color)

Copy Resolution (dpi)

600 x 600

Copy Size Platen: Up to Letter

ADF: Up to Legal Multiple Copies Up to 999 Copies

Magnification

25% - 400% (1% Increments)

**Preset Reductions** 25%, 50%, 64%, 78% **Preset Enlargements** 129%, 200%, 400% Copy Features

Paper Setting, Favorite Setting, Two-sided, Original Type Selection, Cancel, N-on-1, Density Adjustment, Sharpness,

Erase Frame, Collate, Copy ID Card

Scan Specifications

Simplex Automatic Document Feeder **Document Feeder Paper Capacity** 

50 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

Legal, Letter, Statement

**Document Feeder Supported Media Weights** 

13-28 lb. Bond (50-105 g/m<sup>2</sup>) Platen Acceptable Originals

Sheet, Book Pull Scan

ScanGear MF for TWAIN, and WIA

Scan Resolution (dpi)

Push Scan: Up to 300 x 600 Pull Scan: Up to 600 x 600 Scan-to-Mobile Devices

Canon PRINT Business Scan Speed (Letter)

Single-sided: 14/28 ipm (300 x 600 dpi) (Color/BW)

Memory Media

Standard USB Memory (JPEG, TIFF, PDF)

Send Specifications

Destination

Email/Internet FAX (SMTP), SMB, FTP

Address Book

LDAP (50)/Local (300)/Speed Dial (281)

Send Resolution (dpi)

600 x 600 (Pull Scan), 196 x 204 (iFax), 300 x 300 (Other)

**Communication Protocol** FTP, SMB

Email/iFax: SMTP, POP3, iFax (Simple)

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable)

PDF (Encrypted, Digital Signature) Optional:

Security Specifications

Authentication

Department ID Authentication Standard:

Network

IP/MAC Address Filtering, IPSEC, TLS Standard:

> Encrypted Communication, SNMP V3.0, IEEE 802.1X (Wired Only), IPv6, SMTP Authentication, POP Authentication, POP Authentication before SMTP

Document

Standard: Secure Print Wi-Fi Authentication Methods

Infrastructure WEP 64/128 bit, WPA-PSK (TKIP/AES),

Mode: WPA2-PSK (AES)

Wi-Fi Access

WPA2-PSK (AES) Point:

**Environmental Specifications** 

**Operating Environment** Temperature: 50 to 86° F

20 to 80% RH (no condensation) Humidity:

**Power Requirements** AC 120-127 V:6.5 A, 60 Hz

**Power Consumption** Maximum: Approx. 1470 W Standby: Approx. 20.5 W Sleep Mode: Approx. 0.6 W 0.31 kWh

Typical Electricity Consumption (TEC) Rating: Standards

ENERGY STAR @Qualified, Rated EPEAT Silver1



(305) 256-9304 info@completeoffice.co









