

BROWARD 954.800.3130

MIAMI-DADE 305.256.9304

PALM BEACH 561.508.9778

## Canon

## **IMAGECLASS MF429DW**

FAST 40 PAGES PER MINUTE IN BLACK & WHITE



5" COLOR TOUCHSCREEN WITH SMARTPHONE LIKE USABILITY

REMOTELY CONTROL DEVICE ACCESS



FIRST PRINT-OUT TIME AS FAST AS 6 SECONDS

SUPPORTS MOBILE SOLUTIONS FOR PRINTING AND SCANNING

HIGH-CAPACITY, ALL-IN-ONE CARTRIDGE HELPS REDUCE COSTS

VISIT US AT COMPLETEOFFICE.CO



Main Unit

Core Functions

Standard: Print, Copy, Scan, Send, Fax

Processor

Canon Custom Processor

Control Panel

5" Color Touch Panel

Memory

Standard Interface Connection

USB 2.0 x2 (Host), USB 2.0 x1 (Device) High-Speed, 10/100/1000Base-T Ethernet (Network), Wi-Fi 802.11b/g/n, Wi-Fi® Direct Connection

Paper Capacity (Letter, 20 lb. Bond)

Standard: 350 Sheets Maximum: 900 Sheets

Paper Sources (Letter, 20 lb. Bond)

Standard: 250-sheet Paper Cassette, 100-sheet

Stack Bypass
Optional: 550-sheet Paper Cassettes
(Cassette Unit-AH1)

Paper Output Capacity (Letter, 20 lb. Bond)

Standard: 65 Sheets

Supported Media Types

Cassettes: Thin, Plain, Recycled, Thick, Bond Stack Bypass: Thin, Plainr, Recycled, Thick, Bond, Label, Envelope (10 Envelopes)

Supported Media Sizes

Cassettes: Letter, Legal, Statement, Executive
Custom (Min. 4.1" x 5.8" to Max. 8.5" x 14")
Stack Bypass: Letter, Legal, Statement, Executive

Envelope: COM10, Monarch, C5, DL Custom (Min. 3" x 5" to Max. 8.5" x 14")

Supported Media Weights

Cassettes: 14 lb. Bond to 32 lb. Bond (52 to 120 g/m²) Stack Bypass 14 lb. Bond to 43 lb. Bond (52 to 163 g/m²)

Warm-up Time

From Power On: 14 Seconds or Less From Sleep 4 Seconds or Less Mode:

Dimensions (W x D x H)

Standard 17.9" x 18.3" x 15.5"

(Desktop): (453 mm x 464 mm x 392 mm)

Installation Space (W x D x H)

Standard (Desktop): 21.8" x 38.7" x 28.6" (553 mm x 983 mm x 664 mm) Fully Configured: 21.8" x 38.7" x 43.9"

(553 mm x 983 mm x 795 mm)

Weight

Machine Only: Approx. 35.8 lb. (16.2 kg)
Boxed Weight: Approx. 45.9 lb. (20.8 kg)

**Print Specifications** 

Printing Method

Laser Beam Printing

Print Speed<sup>4</sup>

Up to 40 ppm (Letter); Up to 32 ppm (Legal)

**First-Print-Out Time** Approx. 6 Seconds

Recommended Monthly Page Volume

500 - 4,000 Pages

Print Resolution (dpi)

600 × 600

Standard Page Description Languages

UFR II, PCL<sup>®</sup>6, PCL<sup>®</sup>5, Adobe PostScript 3<sup>®</sup>

Double-Sided Printing

Automatic (Standard)

Direct Print

Available from USB Memory (JPEG, TIFF, PDF)

Printing from Mobile and Cloud-based Services<sup>5</sup>

Apple® AirPrint,® Canon PRINT Business, Mopria™ Print Service, Google Cloud Print,™ uniFLOW Secure Mobile Printing Fonts

PCL: 93 Fonts PS: 136 Fonts Operating System

UFR II/ Windows® 7/Windows 8.1/Windows 10/ PCL/PS: Windows Server 2008/Windows Server

2008 R2/Windows Server 2012/Windows Server 2012 R2/Windows Server 2016

Mac OS X v10.8.5 (or later)

**Copy Specifications** 

Copy Speed

Up to 40 ppm (Letter); Up to 32 ppm (Legal)

First-Copy-Out Time (Letter)

Approx. 6.0 Seconds

Copy Resolution (dpi)

600 x 600

Copy Size

Platen: Up to Letter ADF: Up to Legal **Multiple Copies** 

Up to 999 Copies

Magnification

25% - 400% (1% Increments)

Preset Reductions 25%, 50%, 64%, 78% Preset Enlargements 129%, 200%, 400%

Copy Features

Paper Setting, Favorite Settings, Two-sided, Original Type Selection, Cancel, N-on-1, Density Adjustment, Sharpness, Erase Frame, Collate, Copy ID Card

Scan Specifications

Туре

Single-Pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** 

50 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

Legal, Letter, Statement

Document Feeder Supported Media Weights

Single and Double-sided scanning: 13-28 lb. Bond

(50-105 g/m<sup>2</sup>)

Platen Acceptable Originals

Sheet, Book
Pull Scan

ScanGear MF for TWAIN, WIA, and ICA

Supported OS

Windows 7/Windows 8.1/Windows 10 / Windows Server 2008/Windows Server 2008 R2/Windows Server 2012/Windows Server 2012 R2/Windows Server 2016/Mac OS X v10.8.5 (or later)

Scan Resolution (dpi) 300 x 600, 600 x 600

C--- t- M-bil- D---i--

Scan-to-Mobile Devices
Canon PRINT Business

Scan Speed (Letter)

Single-sided: 13/38 ipm (300 x 600 dpi) (Color/BW)
Double-sided: 26/70 ipm (300 dpi) (Color/BW)

Memory Media

Standard USB Memory (JPEG, TIFF, PDF)

**Send Specifications** 

Destination

 $Email/Internet\,FAX\,(SMTP),\,SMB,\,FTP,\,Super\,G3\,FAX$ 

Address Book

LDAP (50)/Local (300)/Speed Dial (281)

Send Resolution (dpi)

 $600 \times 600$  (Pull Scan),  $196 \times 204$  (iFax),  $300 \times 300$  (Other)

Communication Protocol

File: FTP, SMB

Email/iFax: SMTP, POP3, iFax (Simple)

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable)
Optional: PDF (Encrypted, Digital Signature)

Fax Specifications

Modem Speed

Super G3: 33.6 kbps G3: 14.4 kbps Compression Method MH. MR. MMR. JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement to Legal

Fax Memory Up to 512 Pages Speed Dials

Max. 281

Group Dials/Destinations

Max. 299 Dials

Sequential Broadcast Max. 310 Addresses Memory Backup

Yes

Fax Features

RX Mode, Resolution, Two-sided Original, Density, Sharpness, Favorite Settings, Duplex Fax

Security Specifications

Authentication

Standard: Embedded Universal Login Manager,

Department ID Authentication

Optional: uniFLOW, uniFLOW Online

Network

Standard: IP/MAC Address Filtering, IPSEC, TLS

Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP

Authentication before SMTP

Document

Standard: Secure Print

Standard: Secure Print
Optional: Encrypted PDF, User and Device Signatures

Wi-Fi Authentication Methods

Wi-Fi

Infrastructure WEP 64/128 bit, WPA-PSK (TKIP/AES),

Mode: WPA2-PSK (AES)

Wi-Fi Access

ccess WPA2-PSK (AES)

**Environmental Specifications** 

Operating Environment

Temperature: 50 to 86° F Humidity: 20 to 80% RH (no condensation)

Power Requirements
AC 120-127 V:6.5 A, 60 Hz
Power Consumption

Maximum: Approx. 1320 W Standby: Approx. 10 W Sleep Mode: Approx. 0.9 W

Typical Electricity Consumption (TEC) Rating:

Standards

ENERGY STAR® Qualified, Rated EPEAT Silver

1.3 kWh