



**COMPLETE**  
*Office.co*

TECHNOLOGY AT WORK

BROWARD 954.800.3130

MIAMI-DADE 305.256.9304

PALM BEACH 561.508.9778

# Canon

## IMAGECLASS MF424DW

FAST 40 PAGES PER MINUTE IN  
BLACK & WHITE



5" COLOR TOUCHSCREEN WITH  
SMARTPHONE LIKE USABILITY

PRINT UP TO 8-1/2" x 14"  
(LEGAL SIZE)

FIRST PRINT-OUT TIME AS  
FAST AS 6 SECONDS

SUPPORTS MOBILE SOLUTIONS  
FOR PRINTING AND SCANNING



A UNIQUE, CUSTOMIZED DEVICE  
EXPERIENCE WITH  
APPLICATION LIBRARY

VISIT US AT

**COMPLETEOFFICE.CO**



## Main Unit

### Core Functions

Standard: Print, Copy, Scan, Send, Fax

### Item Code

MF426dw: 2222C002  
MF424dw: 2222C003

### Processor

Canon Custom Processor

### Control Panel

5" Color Touch Panel

### Memory

1 GB

### Standard Interface Connection

USB 2.0 x2 (Host), USB 2.0 x1 (Device) High-Speed, 10/100/1000Base-T Ethernet (Network), Wi-Fi 802.11b/g/n, Wi-Fi® Direct Connection

### Paper Capacity (Letter, 20 lb. Bond)

Standard: 350 Sheets  
Maximum: 900 Sheets

### Paper Sources (Letter, 20 lb. Bond)

Standard: 250-sheet Paper Cassette, 100-sheet Stack Bypass  
Optional: 550-sheet Paper Cassette (Cassette Unit-AH1)

### Paper Output Capacity (Letter, 20 lb. Bond)

Standard: 65 Sheets

### Supported Media Types

Cassettes: Thin, Plain, Recycled, Thick, Bond  
Stack Bypass: Thin, Plain, Recycled, Thick, Bond, Label, Envelope (10 Envelopes)

### Supported Media Sizes

Cassettes: Letter, Legal, Statement, Executive Custom (Min. 4.1" x 5.8" to Max. 8.5" x 14")  
Stack Bypass: Letter, Legal, Statement, Executive Envelope: COM10, Monarch, C5, DL Custom (Min. 3" x 5" to Max. 8.5" x 14")

### Supported Media Weights

Cassettes: 14 lb. Bond to 32 lb. Bond (52 to 120 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 43 lb. Bond (52 to 163 g/m<sup>2</sup>)

### Warm-up Time

From Power On: 14 Seconds or Less  
From Sleep: 4 Seconds or Less  
Mode:

### Dimensions (H x W x D)

Standard: 17.9" x 18.3" x 15.5"  
(Desktop): (453 mm x 464 mm x 392 mm)

### Installation Space (H x W x D)

Standard: 19.5" x 38.7" x 30.0"  
(Desktop): (453 mm x 983 mm x 764 mm)  
Fully Configured: 19.5" x 38.7" x 35.3"  
(453 mm x 983 mm x 895 mm)

### Weight

Machine Only: Approx. 35.8 lb. (16.2 kg)  
Boxed Weight: Approx. 45.9 lb. (20.8 kg)

## Print Specifications

### Printing Method

Laser Beam Printing

### Print Speed<sup>2</sup>

Up to 40 ppm (Letter); Up to 32 ppm (Legal)

### First-Print-Out Time

Approx. 6 Seconds

### Recommended Monthly Page Volume

500 - 4,000 Pages

### Print Resolution (dpi)

600 x 600

### Standard Page Description Languages

UFR II, PCL®6, PCL®5, Adobe PostScript 3® (MF426dw only)

### Double-Sided Printing

Automatic (Standard)

### Direct Print

Available from USB Memory (JPEG, TIFF, PDF)

### Printing from Mobile and Cloud-based Services<sup>3</sup>

Apple® AirPrint®, Canon PRINT Business, Mopria™ Print Service, Google Cloud Print™<sup>4</sup>

### Fonts

PCL: 45 Fonts  
PS: 136 Fonts (MF426dw only)

### Operating System

UFR II/ PCL/PS: Windows® 7/Windows 8.1/Windows 10/ Windows Server 2008/Windows Server 2008 R2/Windows Server 2012/Windows Server 2012 R2/Windows Server 2016  
Mac OS X v10.8.5 (or later)

## Copy Specifications

### Copy Speed

Up to 40 ppm (Letter); Up to 32 ppm (Legal)

### First-Copy-Out Time (Letter)

Approx. 6.0 seconds

### Copy Resolution (dpi)

600 x 600

### Copy Size

Platen: Up to Letter  
ADF: Up to Legal

### Multiple Copies

Up to 999 Copies

### Magnification

25% - 400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 78%

### Preset Enlargements

129%, 200%, 400%

### Copy Features

Paper Setting, Favorite Settings, Two-sided, Original Type Selection, Cancel, N-on-1, Density Adjustment, Sharpness, Erase Frame, Collate, Copy ID Card

## Scan Specifications

### Type

Single-Pass Duplexing Automatic Document Feeder

### Document Feeder Paper Capacity

50 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

Legal, Letter, Statement

### Document Feeder Supported Media Weights

Single and Double-sided scanning: 13-28 lb. Bond (50-105 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book

### Pull Scan

ScanGear MF for TWAIN, WIA, and ICA

### Supported OS

Windows 7/Windows 8.1/Windows 10/Windows Server 2008/Windows Server 2008 R2/Windows Server 2012/Windows Server 2012 R2/Windows Server 2016 / Mac OS X v10.8.5 (or later)

### Scan Resolution (dpi)

300 x 600, 600 x 600

### Scan-to-Mobile Devices

Canon PRINT Business

### Scan Speed (Letter)

Single-sided: 13/38 ipm (300 x 600 dpi) (Color/BW)  
Double-sided: 26/70 ipm (300 dpi) (Color/BW)

### Memory Media

Standard USB Memory (JPEG, TIFF, PDF)

## Send Specifications

### Destination

Email/Internet FAX (SMTP), SMB, FTP, Super G3 FAX

### Address Book

LDAP (50)/Local (300)/Speed Dial (281)

### Send Resolution (dpi)

600 x 600 (Pull Scan), 196 x 204 (iFax), 300 x 300 (Other)

### Communication Protocol

File: FTP, SMB  
Email/iFax: SMTP, POP3, iFax (Simple)

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable)

## Fax Specifications

### Modem Speed

Super G3: 33.6 kbps  
G3: 14.4 kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

### Sending/Recording Size

Statement to Legal

### Fax Memory

Up to 512 Pages

### Speed Dials

Max. 281

### Group Dials/Destinations

Max. 299 Dials

### Sequential Broadcast

Max. 310 Addresses

### Memory Backup

Yes

### Fax Features

RX Mode, Resolution, Two-sided Original, Density, Sharpness, Favorite Settings, Duplex Fax

## Security Specifications

### Authentication

Standard: Department ID Authentication

### Network

Standard: IP/MAC Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

### Document

Standard: Secure Print

### Wi-Fi Authentication Methods

Wi-Fi Infrastructure: WEP 64/128 bit, WPA-PSK (TKIP/AES), Mode: WPA2-PSK (AES)  
Wi-Fi Access Point: WPA2-PSK (AES)

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86° F  
Humidity: 20 to 80% RH (no condensation)

### Power Requirements

AC 120-127 V:6.5 A, 60 Hz

### Power Consumption

Maximum: Approx. 1320 W  
Standby: Approx. 10 W  
Sleep Mode: Approx. 0.9 W  
Typical: 1.3 kWh  
Electricity Consumption (TEC) Rating:

### Standards

ENERGY STAR® Qualified, Rated EPEAT Silver